

M50

**Rubber/Plastics/Cork/Carpet Tiling/Sheeting  
To be read with Preliminaries/General Conditions**

130

Manufacturers: Westbond Ltd.  
Cortonwood Business Park  
Cortonwood Drive  
Brampton, Barnsley  
S73 0UF

Contact: **UK** **T: +44 (0) 20 7553 9300** **F: +44 (0) 20 7553 9309**  
**Export** **T: +44 (0) 1226 757757** **F: +44 (0) 1226 757759**

[info@westbond-carpets.com](mailto:info@westbond-carpets.com)  
[www.westbond-carpets.com](http://www.westbond-carpets.com)

**Product:** N9000XL  
**Surface Yarn:** Invista Antron  
**Construction:** I Bonding  
**Pile Weight:** 950 g/m<sup>2</sup>  
**Effective Pile Height:** 5.1 mm  
**Pile Density:** 0.149 g/cm<sup>3</sup>  
**Tufts Per m<sup>2</sup>:** 272,000  
**Total Weight:** 4,000 g/m<sup>2</sup>  
**Total Thickness:** 8.5 mm  
**Tile Size:** 500 x 500 mm  
**Tile Size Specification:** <+/-0.2%  
**Dimensional Stability:** <0.1%  
**Squareness:** <+/-0.1%  
**Damage At Cut Edges:** EN 0  
**Curling:** 0  
**Usage Area:** Heavy Contract  
**Usage Class:** 4 (EN 1307)  
**Comfort Class:** 4 (EN 1307)  
**Castor Chair:** r>2.4 (EN 985)  
**Antistatic:** IBM/ICL  
**Walking Test:** <2.0 kV  
**Impact Sound:** DIN 52210, 31 dB  
**Sound Absorption:** DIN 52212  
**Flammability:** EN 13501 Class Bfl – s1  
ASTM E648  
**Method of Laying:** Directional

Special tile size available on request. Manufacturing specifications subject to normal industry tolerances. Westbond Ltd. reserve the right to change specifications without notice. Final product may vary - within commercial tolerances - from sample.